

DYNAMAXX[®]



ALL TRACTION E-4



- REDUCED WHEEL SPIN & EXCELLENT TRACTION

- SELF-CLEANING TREAD

- LONGER TIRE LIFE

- LOW ROAD NOISE AND REDUCED VIBRATION

- EXCELLENT RESISTENCE TO DAMAGE

- IMPROVED OPERATOR COMFORT



E-4 tyre, suitable for earth moving vehicles. Its aggressive, self-cleaning deep tread design provides excellent traction in tough, rigid dump truck applications.



Size	LI / SS	SR	Type	Rim	Unit	Tread Depth	Section Width	Overall Diameter
14.00R24	169B	***	TT	10.00 W	in.	46/32	15.6	55.1
					mm	36	395	1400
14.00R25	169B	***	TT/TL	10.00/1.5	in.	46/32	15.6	55.1
					mm	36	395	1400
18.00R33	191B	**	TL	13.00/2.5	in.	66/32	20.3	73.6
					mm	52	516	1876
21.00R33	200B	**	TL	15.00/3.0	in.	77/32	21.8	78.0
					mm	61	554	1982
21.00R35	201B	**	TL	15.00/3.5	in.	74/32	23.2	80.7
					mm	59	590	2050
24.00R35	209B	**	TL	17.00/3.5	in.	83/32	26.2	85.4
					mm	66	666	2170

NOTES _____

