

FLOTATION FORESTRY

FF FORESTRY FLOTATION [TRA CODE: HF-2] STEEL BELT

CHARACTERISTICS

- large ground contact area
- low pressure ratio to the ground
- less damage to soil and sapling
- good self-cleaning
- excellent traction
- slide-slippage proof
- best resistance to punctures
- classic lug tread for soil protection and long life expectancy
- carcass reinforced with steel belt



tyre size	P.R.	type		tread depth		standard rim	inflated dimensions				load capacity	
		TT	TL	mm	inch		overall width		overall diameter		max. speed 30km/h	
		TT	TL	mm	inch		mm	inch	mm	inch	load kg	inflation kpa
500/60-22.5	16	Δ	Δ	35	1,38	16	503	19,8	1171	46,1	3000	320
600/50-22.5	16	Δ	Δ	35	1,38	20	601	23,7	1171	46,1	3480	320
700/45-22.5	16	Δ	Δ	35	1,38	24	700	27,6	1171	46,1	4010	320
22/65-25	16	Δ	Δ	24	0,94	17.00/1.7(2.0)	555	21,9	1362	53,6	5290	325
600/55-26.5	16	Δ	Δ	40	1,57	20	610	24	1344	52,9	4550	400
	20	Δ	Δ								5510	500
650/65-26.5	16	Δ	Δ	35	1,38	20	658	25,9	1476	58,1	6290	400
	20	Δ	Δ								7170	500
700/50-26.5	16	Δ	Δ	40	1,57	24	710	28	1344	52,9	5220	400
	20	Δ	Δ								6420	500
750/55-26.5	16	Δ	Δ	35	1,38	24	758	29,8	1476	58,1	6850	400
	20	Δ	Δ								7810	500
800/40-26.5	12	Δ	Δ	40	1,57	28	810	31,9	1344	52,9	4940	320
	16	Δ	Δ								5630	400
	20	Δ	Δ								6420	500
600/60-30.5	12	Δ	Δ	40	1,57	20	600	23,6	1500	59,1	3970	200
	16	Δ	Δ								4640	260
	20	Δ	Δ								5340	330
700/50-30.5	12	Δ	Δ	40	1,57	24	700	27,5	1500	59,1	4230	170
	16	Δ	Δ								4910	220
	20	Δ	Δ								5665	280
800/45-30.5	12	Δ	Δ	40	1,57	28	800	31,5	1500	59,1	4640	170
	16	Δ	Δ								5400	220
	20	Δ	Δ								6090	250

Δ = available X = not available

FF FORESTRY FLOTATION

This is a high flotation forestry tyre with large ground contact area, low-pressure ratio to the ground and less damage to soil and sapling. Tread bars at a certain angle provide good self-cleaning, excellent traction and side slippage-proof. The steel-reinforced carcass gives the best resistance to punctures. Cut-resistant tread areas guarantee a high life expectancy of tyres.

FLOTATION FORESTRY

FF X1 FORESTRY FLOTATION X1 [TRA CODE: HF-2] STEEL BELT

CHARACTERISTICS

- large ground contact area
- low pressure ratio to the ground
- less damage to soil and sapling
- good self-cleaning
- excellent traction
- slide-slippage proof
- steel-reinforced carcass
- best resistance to punctures
- deep tread design and cut-resistant tread for long tyre life
- especially developed for caterpillar treads and linkages



SIZES / TECHNICAL DATA

tyre size	P.R.	type		tread depth		standard rim	inflated dimensions				load capacity	
		TT	TL	mm	inch		overall width		overall diameter		max. speed 30km/h	
							mm	inch	mm	inch	load kg	inflation kpa
650/65-26.5	16	Δ	Δ	35	1,38	20	658	25,9	1476	58,1	6290	400
	20	Δ	Δ								7170	500
750/55-26.5	16	Δ	Δ	35	1,38	24	758	29,8	1476	58,1	6850	400
	20	Δ	Δ								7810	500
710/45-26.5	16	Δ	Δ	30	1,18	24	727	28,62	1326	52,2	5200	400
	20	Δ	Δ								5990	500

Δ = available X = not available

FF X1 FORESTRY FLOTATION X1

These are high flotation forestry tyres with a large ground contact area, low-pressure ratio to the ground and less damage to soil and sapling. Tread bars at a certain angle result in good self-cleaning, excellent traction and side slippage-proof. Its carcass design with Kevlar or steel belt protection gives the best resistance to punctures. Deep tread design and cut-resistant tread compound provide a longer tyre life.